

[29/Mar/2019 Updated Pass 300-165 Exam By Training PassLeader Free 300-165 Study Materials

New Updated 300-165 Exam Questions from PassLeader 300-165 PDF dumps! Welcome to download the newest PassLeader 300-165 VCE dumps: <https://www.passleader.com/300-165.html> (302 Q&As) Keywords: 300-165 exam dumps, 300-165 exam questions, 300-165 VCE dumps, 300-165 PDF dumps, 300-165 practice tests, 300-165 study guide, 300-165 braindumps, Implementing Cisco Data Center Infrastructure (DCII) Exam P.S. New 300-165 DCII dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpMVRmUUJZRWU3cU0 >> New 300-160 DCID dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpeVaktaU1qdFl4WGs >> New 300-170 DCVAI dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpNVNCbDRrNUN3NWM >> New 300-175 DCUCI dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpcTYwUlg5R2o2Tlk >> New 300-180 DCIT dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpNWtfazZEX1o5eWc NEW QUESTION 289 Which feature must be

configured before you can implement a dynamic ARP inspection to validate an ARP packet? A. unicast RPF B. DHCP snooping C. IP Source Guard D. MACsec encryption Answer: B NEW QUESTION 290 Which two statements about the VRRP are true? (Choose two.)

A. VRRP allows the traffic load to be shared through the use of multiple VRRP groups.

B. When the VRRP is configured to track a Layer 2 interface, the VRRP priority instantly reflects the state of the Layer 2 interface. C. The BFD for the VRRP can be configured only between two Cisco Nexus switches. D. vPC can forward traffic through both VRRP devices. E. The VRRP

can be configured on the management interface. Answer: AD NEW QUESTION 291 Which description of a MAC ACL is true?

A. It filters based on the DSCP value. B. It is applied to egress traffic only.

C. It is applied when DHCP snooping is enabled. D. It is applied to ingress traffic only. Answer: D NEW QUESTION 292 You have a Fibre Channel switch with one of its ports connected to a host. The host

remains in the initializing state. What is the most likely cause of this issue? A. The FLOGI packet was dropped somewhere on the data path. B. The ELP process failed after the FLOGI occurred.

C. The host is not powered on. D. The vFC interface on the host is configured to use an incorrect mode. Answer: A NEW QUESTION 293 Which statement accurately describes EPLD upgrades?

A. A system reboot is required after an EPLD upgrade. B. They should be performed only if advised by the Cisco TAC. C. EPLD upgrades apply only to supervisor modules.

D. They are disruptive to the module to which they are applied. Answer: D NEW QUESTION 294 Which statement about a configuration that uses OSPFv3 multiarea adjacency is true? A. A switch can support more than one address family by using point-to-multipoint. B. switch can operate in more than one area by using subinterfaces. C. Multiple VRFs can operate in different areas. D. The link on a

primary interface can be in more than one area. Answer: B NEW QUESTION 295 Which ACL is applied first when a packet enters a Cisco Nexus Series Switch? A. port ACL B. ingress router ACL

C. SGACL D. ingress VACL Answer: A NEW QUESTION 296 When

configuring PIM on a Cisco Nexus 7000 Series switch, which mode requires you to configure an RP? A. SSM B. DM C. SDM D. BIDIR Answer: D NEW

QUESTION 297 Which database contains information about all of the devices that are currently registered in the fabric?

A. RSCN B. FLOGI C. FDMI D. FCNS Answer: C NEW QUESTION 298 Drag and Drop Drag and drop the optional OSPF parameters from the left onto the

correct functions on the right.

area range	creates a type 5 LSA
default information originate	converts type 7 LSAs to type 5
default metric	summarizes routes between areas
route map	sets all redistributed routes to the same metric
translate <small>www.passleader.com</small>	filters select external routes flooded throughout the NSSA

Answer:

	default metric
	route map
	area range
	translate
	default information originate <small>www.passleader.com</small>

NEW QUESTION 299 You are implementing a Cisco Fabric Path network. Which statement accurately describes the VN-Segment feature? A. The VN-Segment feature must be enabled on all leaf switches. B. Up to 16,000 VN segments are supported on a leaf switch. C. The VN-Segment feature must be enabled on all switches. D. The VN-Segment tag is added to VN-Segment edge ports. Answer: A

NEW QUESTION 300 In Any Source Multicast groups which multicast enabled device supports shared trees? A. RP B. any router in the tree except for the RP C. first-hop router D. last-hop router Answer: C

NEW QUESTION 301 You have multiple OTV edge devices in each OTV site. Which configuration prevents an end-to-end STP loop? A. selective unicast flooding B. AED election C. FHRP filtering D. ARP local caching Answer: B

NEW QUESTION 302 Download the newest PassLeader 300-165 dumps from passleader.com now! 100% Pass Guarantee! 300-165 PDF dumps & 300-165 VCE dumps: <https://www.passleader.com/300-165.html> (302 Q&As) (New Questions Are 100% Available and Wrong Answers Have Been Corrected! Free VCE simulator!) P.S. New 300-165 DCII dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpMVRmUUJZRWU3cU0 >> New 300-160 DCID dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpVhtaU1qdFI4WGs >> New 300-170 DCVAI dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpNVNCbDRrNUN3NWM >> New 300-175 DCUCI dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpcTYwUlg5R2o2Tlk >> New 300-180 DCIT dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpNWtfazZEX1o5eWc