This page was exported from - Free Cisco Training & Resources - Certification Exam Preparation
Export date: Sat Mar 14 3:19:20 2026 / +0000 GMT

CCNA ICND2 Lab 5 - Configure Telnet Remote Access

Lab Topology:

Lab Requirements: 1. The router names are P4S1 and P4S2. 2. Set the privilege password and the vty line password on P4S2. 3. Telnet from P4S1 to P4S2. 4. View other users that telneted to P4S2. **Lab Process:** The configurations of P4S2 are as follows: P4S2(config)#enable secret cisco   / *set enable password* P4S2(config)#line vty 0 4   / *enter the VTY line mode* P4S2(config-line)#login P4S2(config-line)#password cisco   / *set telnet password* P4S2(config-line)#exit P4S2(config)#int s1/1 P4S2(config-if)#ip add 192.168.12.2 255.255.255.0 P4S2(config-if)#clock rate 64000 P4S2(config-if)#no shutdown The configurations of P4S1 are as follows: P4S1(config)#int s1/1 P4S1(config-if)#ip add 192.168.12.1 255.255.255.0 P4S1(config-if)#no shutdown Commands for telneting from P4S1 to P4S2: P4S1#telnet 192.168.12.2 Trying 192.168.12.2 ... Open User Access Verification Password: P4S2>enable Password: P4S2#