

CCNA ICND1 Lab4 - Configure VTP

Lab Tips: VLAN Trunk Protocol (VTP) is a proprietary Cisco protocol that is used to share VLAN configuration information over the trunk link between Cisco switches. VTP allows switches to share and synchronize VLAN information to ensure the consistency of VLAN configuration. **Topology:**



Lab Requirements: 1. Port F0/24 of SW1 is connected with Port F0/24 of SW2. Set the two ports to trunk mode. 2. Set SW1 to VTP server mode and SW2 to VTP client mode. 3. SW1 creates VLAN2. Check whether VLAN information can be synchronized on SW2. 4. Delete VLAN2 on SW2. **Note:** By default, VTP of the switch is enabled. All the servers are in server mode. **Lab Process:** P4S-Switch1#vlan database P4S-Switch1(vlan)#vtp domain pass4sure P4S-Switch1(vlan)#vtp password pass4sure P4S-Switch1(vlan)#vtp server P4S-Switch1(vlan)#vtp mode server P4S-Switch1(vlan)#vtp 2 name p4s2 P4S-Switch1(config)#int fa1/1 P4S-Switch1(config-if)#switchport mode trunk P4S-Switch1(config-if)#no shutdown P4S-Switch2#vlan database P4S-Switch2(vlan)#vtp domain pass4sure P4S-Switch2(vlan)#vtp password pass4sure P4S-Switch2(vlan)#vtp client P4S-Switch2(config)#int fa1/1 P4S-Switch2(config-if)#switchport mode trunk P4S-Switch2(config-if)#no shutdown