

CCSP SNRS Lab3 - Context-Based Access Control

?Lab Topology?



?Lab Object? Technical characteristics: 1. Traffic filtering CBAC checks not only the information of the network layer and the transport layer but also the information of the application layer. It can also filter the http traffic and block java plug-in 2. Traffic monitoring CBAC monitors the traffic passing through the router and handles the TCP and UDP state information which can be used to generate the temporary list to release the rebound traffic and other traffic allowed. 3. Alert and audit 4. Intrusion Prevention

?Lab Process? 1. Configuration of GW

audit-trail	GW(config)#ip access-list ex ACLIN	GW(config)#ip inspect alert-off	GW(config)# ip inspect
inspect name CBAC	tcp alert on audit-trail off [k1]	GW(config-ext-nacl)#permit ospf any any	GW(config)# ip
name CBAC	ftp	GW(config)# ip inspect name CBAC udp	GW(config)# ip inspect
java-list 2	urlfilter	GW(config)#ip inspect name CBAC icmp [k2]	GW(config)# ip inspect name CBAC http
GW(config)#interface s0/0	GW(config-if)#ip access-group ACLIN in	GW(config)#access-list 2 deny 218.18.1.0 0.0.0.255	GW(config)#access-list 2 permit any
		GW(config-if)#ip inspect CBAC out	

Adjust the values of timeout and threshold: ip inspect tcp synwait-time *seconds* The default time is 30 seconds, if a TCP connection is not established within this time, this connection will be dropped out. ip inspect tcp finwait-time *seconds* The default time is 5 seconds, if a TCP connection is not established within this time, this connection will be dropped out. ip inspect tcp idle-time *seconds* The default time is 3600 seconds. ip inspect udp idle-time *seconds* The default time is 30 seconds. Monitor the UDP traffic and release the rebound UDP traffic within 30 seconds. ip inspect dns-timeout *seconds* The default time is 5 seconds. The DNS query time. ip inspect max-incomplete high *number* The default number is 500. If the number exceeds 500, the original Half-open connection will be deleted. ip inspect max-incomplete low *number* The default number is 400. Stop deleting if the number is lower than 400. ip inspect one-minute high *number* The default number is 500. Begin to delete the original Half-open connections when the new connection number is up to 500 within a minute. ip inspect one-minute low *number* The default number is 400. Stop deleting the original Half-open connections when the new connection number is lower than 400 within a minute. ip inspect tcp max-incomplete host *number* block-time *minutes* Control the number of the half-open connections based on the single host, the default is host 50 block-time 0. block-time = 0, if the TCP half-open connection number based on the single host exceeds the configured value, the oldest half-open connections will be cleared when there are new connection requests. block-time >0, when the TCP half-open connection number based on the single host exceeds the configured value, clear all the original half-open connections if there are new connection requests and block all the new connection requests within the block-time. 2. Test: Telnet the outside router from the inside router and examine the generation of the list on the gateway router.

access-list	show ip inspect config	show ip inspect all	show ip inspect sessions detail	Configure
logging:	GW(config)#logging host 192.168.1.254	GW(config)#logging trap informational		
GW(config)#no ip inspect [k3]	[k1]Switch for some protocol alert and audit	[k2]The higher version can inspect ICMP without releasing ICMP on the external interface	[k3]Close CBAC and clear CBAC configurations.	