

[New Exam Dumps New Released 269q 642-437 VCE and PDF Practice Test For Free

Being worried about passing your 642-437 exam? Why not trying PassLeader's 642-437 vce or pdf dumps? We PassLeader now are offering the accurate 269q 642-437 exam questions and answers, you can get all the real exam questions from our 642-437 exam dumps. All our 269q 642-437 practice tests are the newest and same with the real test. We ensure that you can pass 642-437 exam easily after getting our premium 642-437 study guide! Now visit passleader.com to get the valid 642-437 braindumps with free version VCE Player! keywords: 642-437 exam, 269q 642-437 exam dumps, 269q 642-437 exam questions, 642-437 pdf dumps, 642-437 vce dumps, 642-437 braindumps, Implementing Cisco Voice Communications and QoS v8.0 (CVOICE v8.0)



NEW QUESTION 221 A small office needs to provide outbound dialing and inbound DID without the cost of a T1 circuit. All signaling is loop-start. Which analog port configuration will support these requirements? A. voice-port 0/0/0 description fxs-did signal did loop-start ! voice-port 0/1/0 description fxo signal loop-start ! dial-peer voice 1 pots incoming called-number . direct-inward-dial port 0/0/0 ! dial-peer voice 90 pots destination-pattern 9T port 0/1/0 B. voice-port 0/0/0 signal loop-start ! voice-port 0/1/0 signal loop-start ! dial-peer voice 1 pots incoming called-number T direct-inward-dial ! dial-peer voice 90 pots destination-pattern 9T port 0/1/0 C. voice-port 0/1/0 signal did loop-start ! dial-peer voice 1 pots incoming called-number . ! dial-peer voice 90 pot destination-pattern 9T port 0/1/0 D. voice-port 0/0/0 signal did loop-start ! dial-peer voice 1 pots incoming called-number . direct-inward-dial ! dial-peer voice 90 pots destination-pattern 9T port 0/0/0 Answer: A

NEW QUESTION 222 A voice gateway has the isdn switch-type command in the global configuration and on the T1 signaling channel. Which configuration takes precedence if the two configurations are different? A. The configuration in the global configuration always takes precedence over the interface configuration. B. The voice gateway parses the configuration from top to bottom and will use the first isdn switch-type entry. C. The voice gateway will use the isdn switch-type command that matches the ISDN switch that is connected to the T1 controller. D. The configuration in the T1 controller portion of the Cisco IOS configuration takes precedence over the isdn switch-type command in the global configuration. E. The configuration under the ISDN signaling channel takes precedence over the isdn switch-type command in the global configuration. Answer: E

NEW QUESTION 223 What is the reason that a call succeeds when COR is applied to the incoming dial peer and is equal to or greater than the COR settings that are applied to the outgoing dial peer? A. The COR list for incoming calls on the incoming dial peer is a superset of COR lists for outgoing calls on the outgoing dial peer. B. COR lists for incoming calls on the incoming dial peer are not a superset of COR lists for outgoing calls on the outgoing dial peer. C. The outgoing dial peer, by default, has the lowest priority. D. The incoming dial peer, by default, has the highest COR priority when no COR is applied. Answer: A

NEW QUESTION 224 Calls are failing to reach the E1 PRI circuit on the PSTN gateway. Which command would be useful in determining if the dial peers are configured properly? A. debug voice dial-peer B. debug isdn q921 C. ccapi inout D. show controller e1 0/0/0 E. debug voice circuit Answer: A

NEW QUESTION 225 Refer to the exhibit. When an inbound PSTN call from 4087071222 arrives at the ISDN port that is shown in the exhibit, which dial peer will be matched for the inbound leg?

```
!
dial-peer voice 123 pots
destination-pattern 4087071222
direct-inward-dial
port 0/0/0:23
!
!
dial-peer voice 2123 pots
answer-address 4087071222
port 0/0/0:23
!
voice-port 0/0/0:23
```

www.passleader.com

A. Dial-peer 123, because incoming called-number takes precedence over answer-address.
B. Dial-peer 2123, because answer-address takes precedence over incoming called-number.
C. The matching inbound dial peer will be selected at random. D. Although dial-peer 123 takes precedence, there is no direct-inward-dial that is configured, therefore 2123 will be selected. E. Although dial-peer 123 takes precedence, there is no port that is configured under dial-peer 123, therefore dial-peer 2123 will be selected. Answer: A

NEW QUESTION 226 Which four interworking call flows are associated with a Cisco Unified Border Element using media flow-around? (Choose four.) A. H.323 fast start to H.323 fast start
B. H.323 slow start to SIP delayed offer C. SIP early offer to SIP delayed offer
D. SIP delayed offer to SIP delayed offer E. H.323 fast start to H.323 slow start
F. SIP early offer to H.323 fast start Answer: ACDE

NEW QUESTION 227 Which three methodologies are specific types of QoS used on a 512-kb/s point-to-point IP WAN link? (Choose three.) A. header compression B. FRF.12 C. LLQ D. Multilink PPP
E. RSVP Answer: ABC

NEW QUESTION 228 What are the three acceptable values for one-way delay, jitter, and packet loss in a VoIP network? (Choose three.) A. 0-400 ms for delay B. 1 packet loss C. 20 ms for jitter D. 0-150 ms for delay E. 1 percent packet loss F. 30 ms for jitter Answer: AEF

NEW QUESTION 229 How does DiffServ deliver QoS across the network? A. DiffServ classifies and marks traffic at each node in the network.
B. When using DiffServ, the network tries to deliver a particular kind of service that is based on the QoS that is specified by each packet. C. DiffServ tries to deliver a particular level of service on a per-flow basis across the network. D. DiffServ delivers a particular kind of service based on either a flow-based behavior or a per-hop behavior, depending on how the traffic was marked and classified at ingress. Answer: A

NEW QUESTION 230 When marking traffic for Expedited Forwarding, how does a device that is not capable of recognizing DSCP interpret the EF binary string 101110? A. The device that cannot recognize DSCP will use best effort to forward the packet.
B. The device that does not recognize DSCP will use 110 as the CoS value and forward the packet with a CoS of 6. C. The first device in the network that does not recognize DSCP will use 110 as the CoS value and will replace the DSCP value with a CoS of 6 and forward the packet. D. The devices in the network that do not recognize DSCP will use the three high-order DSCP bits as the CoS setting, resulting in a CoS value of 5. Answer: D

Why Not T

Pass4su



Not Available

Not In Stock

<http://www.passleader.com/642-437.html>