[June-2017 Dumps Valid PassLeader 305q 400-351 Exam Questions With VCE and PDF Download

New Updated 400-351 Exam Questions from PassLeader 400-351 PDF dumps! Welcome to download the newest PassLeader 400-351 VCE dumps: http://www.passleader.com/400-351.html (305 Q&As) Keywords: 400-351 exam dumps, 400-351 exam questions, 400-351 VCE dumps, 400-351 PDF dumps, 400-351 practice tests, 400-351 study guide, 400-351 braindumps, CCIE Wireless Written Exam, v3.1 P.S. New 400-351 dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpWTFGcGFzN0JuYkE >> New CCIE Routing and Switching 400-101 dumps PDF·

https://drive.google.com/open?id=0B-ob6L_QjGLpfnRCUEFYcEhWZUw3OGNQY2FUSkptUXBrZDVzeE8zdkJQUERtOUFINDBFQW8 >> New CCIE Service Provider 400-201 dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpVkYtTGdtRWFodXM >> New CCIE Collaboration 400-051 dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpNnliRG04bG9GbEk >> New CCIE Data Center 400-151 dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpVmo1Q01pZEhTUG8 >> New CCIE Security 400-251 dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpd3JLalNVS0VWbms NEW QUESTION 263 Legacy 802.11b wireless scanners are begin implemented in your autonomous AP deployment. Existing modern clients work fine on the same SSIDs, APs, and channel the legacy scanner are having difficulty maintaining reliable wireless connectivity. Which AP configured could potential correct this issue? A. Enable short preamble Dot11Radio0 B. Disable short 802.11n support is disable E. Configure global preamble negotiation F. Enable short preamble on Dot11Radio1 Answer: C NEW QUESTION 264 You are deploying a high-density wireless setup in a conference center using Cisco Aironet 3700iAPs as you have no Cisco air not 3700e APs available. The power levels for all the APs should be set between 4 and 5. Which configuration option is needed to achieve this goal.? A. Select the TPC values between 4 dBm and 8 dBm B. Manually configure the power levels of the 802.11b and 802.11a radios of all APs either 4 or 5 C. Select the TPC values between 4 dBm and 5 dBm D. Select the TPC values between 11 dBm and 8 dBm Answer: B NEW OUESTION 265 While configuring Wireless Domain Services, which port is used for traffic between infrastructure APs and the WDS AP? A. Generic Routing Encapsulation GRE which IP protocol is 47 B. UDP destination and source protocol port 1812 (0x0714) C. UDP destination and source protocol port 2887 (0x0B47) or Ethernet Type 34605 (0x872D) D. UDP destination and Source Protocol port 1645 (0x066D) Answer: C NEW QUESTION 266 Assuming that the antenna system characteristics (for example, gain VSWR, polarization and beam width) are similar for a 5-GHz and 2.4-GHz radio. While conducting a dual band site survey, how to configure the 5-GHz radio, relative to the 2.4-GHz radio, in order to achieve similar cell size? A. The 5-GHz radio power level should be higher than the 2.4-GHz radio B. The 5-GHz radio should use BPSK modulation and the 2.4 GHz radio should use CCK modulation C. The 5-GHz radio power level should be lower than the 2.4-GHz radio D. The 5-GHz radio should use CCK modulation and the 2.4-GHz radio should use BPSK modulation **Answer: A NEW QUESTION 267** For the following cipher suites, which were defined in the IEEE 802.11i-2004 standard and then again in the 802.11-2007 standard? (Select all that apply.) A. TKIP B. WEP-40 C. TCP-IP D. WEP-104 E. AES-CCMP Answer: ABDE **NEW QUESTION 268** Which two actions will happen when a wireless client deploys a Layer 2 roam between two WLCs with management IP addresses on different IP subnets but dynamic interfaces in the same VLAN? (Choose two.) A. The new WLC exchanges mobility messages with the original WLC and the client database entry is moved to the new WLC. B. The original WLC marks the client with an "Anchor" entry in its own client database. C. The client database entry is maintained on both the original and new WLCs. D. The client database entry is removed from the original WLC once it has been entered into the new WLC. Answer: AD NEW **OUESTION 269** How to monitor CPU utilization on a wireless LAN Controller? A. Define the network management system and community in the WLC and a matching v1 or v2 community-string in the network management system to enable the WLC CPU OID to be polled. B. Define the network management system as a trap receiver and enable the default RFC 1213 traps, which include Sys CPU Utilization. C. Define the network management

system in the WLC with a matching read-write SNMP community to enable the WLC CPU OID to be polled with an SNMP set by

the network management system. D. Define an external syslog receiver in the WLC that will receive a syslog message when the percentage of CPU processing ability reaches a preconfigured percentage. **Answer: A NEW QUESTION** 270 ?? Download the newest PassLeader 400-351 dumps from passleader.com now! 100% Pass Guarantee! 400-351 PDF dumps & 400-351 VCE dumps: http://www.passleader.com/400-351.html (305 Q&As) (New Questions Are 100% Available and Wrong Answers Have Been Corrected! Free VCE simulator!) P.S. New 400-351 dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpWTFGcGFzN0JuYkE >> New CCIE Routing and Switching 400-101 dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpfnRCUEFYcEhWZUw3OGNQY2FUSkptUXBrZDVzeE8zdkJQUERtOUFINDBFQW8 >> New CCIE Service Provider 400-201 dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpVkYtTGdtRWFodXM >> New CCIE Collaboration 400-051 dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpNnliRG04bG9GbEk >> New CCIE Data Center 400-151 dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpVmo1Q01pZEhTUG8 >> New CCIE Security 400-251 dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpd3JLalNVS0VWbms