

CCNA(640-802) Hotspot: Topology Based Questions







Question 2: Users on the 192.168.1.0 /24 network must access files located on the server 1. What route could be configured on router R1 for the file requests to reach the server? **Answer: ip route 0.0.0.0 s 0/0/0** Explanation: To enable users on 192.168.1.0 network to access files on server1, we need to establish a default static route. **Static route syntax:** ip route prefix mask {ip-address interface-type interface-number [ip-address]} [distance] [name] [permanent track number] [tag tag] From the options provided for this question the correct default static route is **ip route 0.0.0** 0.0.0.0 S 0/0/0 **PS:** As per best practices static route to server1 on R1 should have been **ip route 209.165.200.0 255.255.255.0 209.165.100.200** (or) **ip route 209.165.200.0 255.255.255.0 s 0/0/0**

When a packet is sent from Host 1 to Server 1, in how many different frames will the packet be encapsulated as it is sent across the internetwork?

0
1
2
3
4

○ ip route 0.0.0.0 0.0.0.0 s0f000
○ ip route 0.0.0.0 0.0.0.0 209 165.200.226
□ ip route 209.165.200.0 255.255.255.0192.168.1.250
○ ip route 192.168.1.0 255.255.255.0 209.165.100.250

Question 3: When a packet is sent from Host1 to Server1, in how many different frames will the packet be encapsulated as it is sent across the internetwork? **Answer:** 3 Explanation: **First:** Host1 encapsulates the packet into frames and forwards to the switch. Switch in turn forwards the same frame to router R1. **Second:** Router R1 receives the frame on one interface and it is encapsulates into new packet once it leaves the router R1 towards the direction of server1. **Third:** R2 receives this packet and it also encapsulates the frame into new packet when it is forwarded to server1 on different interface of R2. Therefore the packet is sent using three different frames to reach from Host1 to server1.

What must be configured on the network in order for users on the Internet to view web pages located on Web Server 2?

On router R2, configure a default static route to the 192,168.1.0 network.

On router R2, configure DNS to resolve the URL assigned to Web Server 2 to the 192,168.1.10 address.

On router R1, configure NAT to translate an address on the 209,165.100.0/24 network to 192,168.1.10.

On router R1, configure DHCP to assign a registered IP address on the 209,185.100.0/24 network to Veb Server 2.

Question 4: What must be configured on the network in order for users on the internet to view web pages located on web server 2? Answer: On router R1, configure a NAT to translate address on 209.165.100.0 to 192.168.1.0 network.

**The router address 192.168.1.250 is the default of the correct subnet mask for this fo

Question 5: The router address 192.168.1.250 is the default gateway for both web server2 and host 1. What is the correct subnet mask for this network? Answer: 255.255.255.0 Explanation: Given subnet mask for this network is 255.255.255.0 based on the exhibit. To find the correct subnet mask for this network based on number of devices shown in the exhibit that are already configured with IP address and by not wasting IP addresses scheme. The network 192.168.1.0 consists of only three devices as per the exhibits which are configured with IP address. **R1(fa 0/0)**: 192.168.1.250 (default gateway as per the question) **Host1**: 192.168.1.10 **Web server 2**: 192.168.1.106 correct subnet mask that will cover all above IP address is 255.255.255.0 **That is all, hope to helpful for you. Best Luck for ur CCNA 640-802 Exam.** If you need the complete pass4sure test questions for 640-802 Exam, you can visit Latest Pass4sure 640-802.(Pass4sure 640-802 Questions with explaintion) maye it helpful for ur exam.

255.255.255.0 265.256.255.192 255.255.255.250