

[11/Dec/2018 Updated PassLeader Free 300-208 Study Guide With Premium VCE and PDF Dumps Download

New Updated 300-208 Exam Questions from PassLeader 300-208 PDF dumps! Welcome to download the newest PassLeader 300-208 VCE dumps: <https://www.passleader.com/300-208.html> (430 Q&As) Keywords: 300-208 exam dumps, 300-208 exam questions, 300-208 VCE dumps, 300-208 PDF dumps, 300-208 practice tests, 300-208 study guide, 300-208 braindumps, Implementing Cisco Secure Access Solutions (SISAS) Exam P.S. New 300-208 SISAS dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpfkFleG9jUGxxS3kwS0VwcllTWmlxdTIBZUd5cnBkaG5DSE5FbU5yOEYQzQ >> New 300-206 SENS dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpfIBDRGVtd3JJR2k3ZF9sOTAYOHQ0bW1fdlJsZjFwS2xxZmx1TGVRoEdraTA

>> New 300-209 SIMOS dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpVTNFVTRPdC0zTnM >> New 300-210 SITCS dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpTkN0N2xZSHZKY2s NEW QUESTION 391 Which

action do you take to define the global authorization exception policy by using a Device Admin Policy Set?

A. Configure the policy by using Proxy Sequence mode. B. Configure a rule-based condition in a policy set. C. Define the policy for each group of devices. D. Define the policy by configuring a standard profile. Answer: B NEW QUESTION 392 In the redirect URL authorization attribute,

which Cisco ISE node acts as the web server when performing CWA? A. Administration

B. Monitoring C. Policy Service D. pxGrid Answer: C

NEW QUESTION 393 Which two protocols are supported with the Cisco IOS Device Sensor? (Choose two.)

A. SNMP B. Cisco Discovery Protocol C. RADIUS

D. LLDP E. NetFlow Answer: BD NEW QUESTION 394 What sends the redirect ACL that is configured in the authorization profile back to the Cisco WLC? A. Event

B. Cisco-av-pair C. State attribute D. Class attribute

Answer: B NEW QUESTION 395 While troubleshooting a posture assessment issue on a Windows PC, the NAC Agent is not popping up as expected. Which two logs would help in isolating the issue? (Choose two.) A. Cisco

AnyConnect ISE posture logs B. NAC agent logs C. Dart bundle

D. Cisco ISE profiler.log file E. Cisco ISE ise-psc.log file Answer: BE NEW

QUESTION 396 A manager of Company A is hosting a conference. Conference participants use a code on the AUP page of the hot-spot guest portal. Which code must the manager create on Cisco ISE before the meeting? A. user code

B. pass code C. access code D. registration code Answer: D

NEW QUESTION 397 Which command is needed to enable dot1x globally on the switch? A. aaa

authentication dot1x default group radius B. dot1x system-auth-control C. dot1x pae authenticator D. authentication port-control auto Answer: C NEW QUESTION 398 A security engineer

must provision dynamic TrustSec classifications. Which two classification options must the engineer select to accomplish this task? (Choose two.) A. interface B. 802.1X C. MAB

D. IP subnet E. VLAN Answer: BE NEW QUESTION 399 A wireless

deployment must check guest device compliance before allowing access to the network. Which type of guest deployment is needed to allow the Client Provisioning portal? A. central web authentication B. sponsored

C. hotspot D. self-registered Answer: B NEW QUESTION 400 Which

characteristic of an SGFW enforcement policy is true? A. An SGFW has an implicit permit at the beginning.

B. An SGFW has an implicit deny at the end. C. An SGACL has an implicit deny at the end. D. An SGACL has an explicit deny at the beginning. Answer: C NEW QUESTION 401 When

configuring a BYOD portal, which two tasks must be completed? (Choose two.) A. Enable policy services.

B. Create endpoint identity groups. C. Customize device portals.

D. Create a client provisioning portal. E. Create external identity sources. Answer:

AE NEW QUESTION 402 A customer has implemented a BYOD policy to allow employees to use personal devices on the corporate network. Which two methods can an employee use to add their devices to the network? (Choose two.)

A. Client Information Signaling B. My Device Portal C. Client Handshake Authentication

D. Helpdesk Registration E. Native Supplicants

Answer: BD NEW QUESTION 403 Which type of probe is required when using a Cisco IOS Sensor-enabled network switch?

A. Network Scan probe B. HTTP probe C. RADIUS probe
D. NetFlow probe Answer: D NEW QUESTION 404 An organization is deciding between single or dual

SSID solutions for onboarding BYOD devices. Which item must be considered before selecting the dual SSID solution?

A. Wireless coverage is reduced with dual SSIDs. B. Additional access points are
required for dual SSIDs. C. Dedicated controllers are required for dual SSIDs. D.
The second SSID adds channel overhead. Answer: B NEW QUESTION 405 Which two values are compared by the binary

comparison function in authentication that is based on Active Directory? (Choose two.) A. subject alternative
name and the common name B. user-presented password hash and a hash stored in Active Directory

C. user-presented certificate and a certificate stored in Active Directory D.

MS-CHAPv2 provided machine credentials and credentials stored in Active Directory Answer: AD NEW QUESTION 406 A new
consultant must be granted network access for only six months. Which type of ISE default guest account must be used to allow this

access? A. contractor B. temporary C. employee

D. annual Answer: A NEW QUESTION 407 Which two statements about RADIUS are true? (Choose

two.) A. It uses UDP ports 1812 and 1813. B. It encrypts the payload.

C. It encrypts the password only. D. It uses TCP ports 1812 and 1813.

E. It separates authorization and authentication functions. Answer: AC NEW QUESTION 408 Which
method of registering devices on the BYOD My Devices Portal requires that the user have a supplicant installed?

A. MAB B. Single SSID C. Web authentication

D. Dual SSIDs Answer: B NEW QUESTION 409 Which two options are advantages of using the Cisco

IOS Device Sensor as compared to other profiling probes? (Choose two.) A. uses RADIUS authentication
messages to send gathered data to a Cisco ISE server B. provides DHCP information to a Cisco ISE server

without using an IP helper address C. reduces the amount of traffic going to a Cisco ISE server

D. collects switch CPU and RAM usage for monitoring purposes E. replaces all the
other profiling probes Answer: AD NEW QUESTION 410

Download the newest PassLeader 300-208 dumps from
passleader.com now! 100% Pass Guarantee! 300-208 PDF dumps & 300-208 VCE

dumps: https://www.passleader.com/300-208.html (430 Q&As) (New Questions Are 100% Available and Wrong Answers
Have Been Corrected! Free VCE simulator!) P.S. New 300-208 SISAS dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpfkFleG9jUGxxS3kwS0VwcllTWmlxdTIBZUd5cnBkaG5DSE5FbU5yOEpYQzQ
Q >> New 300-206 SENSS dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpfIBDRGVtd3JJR2k3ZF9sOTAYOHQ0bW1fdlJsZjFwS2xxZmx1TGVRoEdraTA
>> New 300-209 SIMOS dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpVTNFVTRPdC0zTnM >> New 300-210

SITCS dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpTkN0N2xZSHZKY2s