

[3/April/2019 Updated Learning New PassLeader 300-170 Exam Questions To Pass Exam Easily

New Updated 300-170 Exam Questions from PassLeader 300-170 PDF dumps! Welcome to download the newest PassLeader 300-170 VCE dumps: https://www.passleader.com/300-170.html (152 Q&As) Keywords: 300-170 exam dumps, 300-170 exam questions, 300-170 VCE dumps, 300-170 PDF dumps, 300-170 practice tests, 300-170 study guide, 300-170 braindumps, Implementing Cisco Data Center Virtualization and Automation (DCVAI) Exam P.S. New 300-170 DCVAI dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpNVNCbDRrNUN3NWM >> New 300-160 DCID dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpeVhtaU1qdFl4WGs >> New 300-165 DCII dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpMVRmUUIJZRWU3cU0 >> New 300-175 DCUCI dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpcTYwUlg5R2o2Tlk >> New 300-180 DCIT dumps PDF: https://drive.google.com/open?id=0B-ob6L_QjGLpNWtfazZEX1o5eWc NEW QUESTION 137 Which two objects must have multicast routing configured when implementing Cisco ACI? (Choose two.) A. Layer 3 In B. Bridge Domain C. SVI D. Leaf E. Layer 3 Out Answer: BD NEW QUESTION 138 You are integrating ten L4-7 devices that share the same configuration arameters and the same service policy mode in your ACI fabric network. Which APIC configuration feature will reduce the configuration overhead fort he L4-7 devices? A. Function Profile B. Device Package C. Graph Connector D. Service Graph Answer: B NEW QUESTION 139 Refer to the exhibit. What is the result of configuration?

```
apic1(config)# leaf 111
apic1(config-leaf)# vrf context tenant Routing vrf Routing
apic1(config-leaf-vrf)# template route-profile RP1
apic1(config-leaf-vrf-template-route-profile)# set as-path pr
```

A. Add AS number 7 after the last AS number in the AS-Path list for all incoming routes to the ACI fabric network. B. Add AS number 7 after the last AS number in the AS-Path list for all the outgoing routes from the ACI fabric network. C. Add AS number seven times for all the incoming routes to the ACI fabric network. D. Add AS number seven times for all the outgoing routes from the ACI fabric network. Answer: D NEW QUESTION 140 Refer to the exhibit. You create a static VLAN pool to be used for VMM integration. On which component do you configure the VLANs in the pool?

```
apic1# configure
apic1(config)# vlan-domain ACI-LAB
apic1(config-vlan)# vlan 2001-3001
```

A. Cisco AVS B. DVS C. Fabric interconnect D. VMware vSwitch Answer: D NEW QUESTION 141 Refer to the exhibit. Which component must you create to deploy the application profile?

```
apic1# configure
apic1(config)# tenant ACI-Lab
apic1(config-tenant)# vrf-context ACILab_v1
apic1(config-tenant-vrf)# exit
apic1(config-tenant)# bridge-domain ACILab_b1
apic1(config-tenant-bd)# vrf member ACILab_v1
apic1(config-tenant-bd)# exit
apic1(config-tenant)# application ACITest
apic1(config-tenant-app-epg)# bridge-domain member ACILab_b1
```

A. Global policy B. Private network C. Domain D. EPG Answer: B NEW QUESTION 142 Which option does a service graph template contain? A. Group of logical devices B. Collection of user steps C. Group of network configurations D. Collection of meta-devices Answer: D NEW QUESTION 143

Which statement describes an endpoint retention policy behaviour of learned endpoints when subnets of a bridge domain are configured to be enforced? A. It removes learned endpoints from the endpoint retention cache when a remote device times out. B. It retains the IP Addresses of the learned endpoint contained outside the bridge subnets.

C. It retains policy information about remote endpoints by using the leaf switches. Answer: A NEW

QUESTION 144 Refer to the exhibit. Which statement accurately describes the configuration of the Cisco2?

```
port-profile C
inherit port-pr
description Par
mtu 9000
max-ports 16
switchport mode
no shutdown
switchport trunl
switchport trunl

port-profile Cis
inherit port-pro
```

A. Cisco2 will be a trunk port. B. The description is Parent_Port.

C. The MTU value is 9000. D. The max-ports value is 16. Answer: A NEW

QUESTION 145 You are attempting to install a switch remotely. You have a POAP script that fails to find a specified boot image on the switch. Which action do you take? A. Abort the provisioning process. B.

Download a copy of the image used by the script. C. Reboot the switch. D. Adjust the script to use any image on the switch. Answer: B NEW

QUESTION 146 Refer to the exhibit. Which description of the configuration of the Cisco Nexus 1000V series switch is true?

```
n1000v (config)# show svcs domain
SVS domain config:
  Domain id:      100
  Control vlan:   190
  Packet vlan:    191
  L2/L3 Aipc mode: L2
  L2/L3 Aipc interface: mgmt0
  Status: Config push to VC successful.
```

A. Packet VLAN is a private VLAN. B. VSM connects to the VMware vCenter server. C. Mgmt0 is a Layer 2 interface. D. SVS mode is set to L3. Answer: C

NEW QUESTION 147 Which two objects can be placed in VRF? A. Console interface

B. Layer 3 subinterfaces C. Layer 2 subinterfaces D. VDC associated to the VRF E. Routing protocol instance Answer: BE NEW

QUESTION 148 Which offer is selected when a Cisco Nexus Series switch multiple DHCP offers during the POAP DHCP discover phase?

A. The offer has the highest TFTP server IP address is selected. B. The first offer is selected. C. An offer is selected randomly. D. The offer has the lowest TFTP server

IP address is selected. Answer: C NEW

QUESTION 149 Which description of the Cisco AVS is true? A. The AVS supports individual interface policies. B. The AVS supports PC, VPC, MAC pinning and FEX interface policies. C. The AVS implements the device package for control plane communication.

D. VLAN or VXLAN encapsulation can be used in No Local Switching mode. Answer: B NEW

QUESTION 150 You are implementing an ACI network with switches that are running the Multiple Spanning Tree Protocol.

Which two actions are required for this configuration? (Choose two.) A. Create MST EPG for the native VLAN to carry the BPDU. B. Map MST instances to interface profiles. C. Create MST Private network for the native VLAN to carry the BPDU. D. Map MST instances to VLANs.

E. Create MST bridge domain for the native VLAN to carry the BPDU. Answer: DE NEW QUESTION 151

You are implementing multicast routing between bridge domains for a client who is running ACI version 3.0 with Nexus ACI first-generation switches. What is required for multicast to operate? A. PIM Any Source Multicast protocol.

B. Bootstrap router for RP to group mapping. C. PIM Source Specific Multicast protocol. D. An external router to perform multicast routing between the bridge domains. Answer: D NEW

QUESTION 152 Download the newest PassLeader 300-170 dumps from passleader.com now! 100% Pass Guarantee! 300-170 PDF dumps & 300-170 VCE dumps: <https://www.passleader.com/300-170.html> (152 Q&As) (New Questions Are 100% Available and Wrong Answers Have Been Corrected! Free VCE simulator!) P.S. New 300-170 DCVAI dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpNVNCbDRrNUN3NWM >> New 300-160 DCID dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpVhtaU1qdFl4WGs >> New 300-165 DCII dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpMVRmUUJZRWU3cU0 >> New 300-175 DCUCI dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpTYwUlg5R2o2Tlk >> New 300-180 DCIT dumps PDF:

https://drive.google.com/open?id=0B-ob6L_QjGLpNWtfazZEX1o5eWc